

DECKMA HAMBURG GmbH

DECKMA Decksmaschinen und Automation Vertriebsgesellschaft in Hamburg mbH

OIL-IN-WATER MONITORS

OMD-15 Series

for Boiler Feedwater and Condensate




Model OMD-15A with Autoclean System

Continuous Monitoring of Oil-in-Condensate

or Oil-in-Boiler Feedwater

The OMD-Series includes a Monitor, the OMD-15, for the control of Oil-in-Boiler Feedwater or Boiler Condensate. This Monitor is type approved by Germanischer Lloyd in accordance with the IMO-



DECKMA HAMBURG GmbH

DECKMA Decksmaschinen und Automation Vertriebsgesellschaft in Hamburg mbH

Resolution MEPC.60 (33) and with the "Technische Regeln für Dampfkessel TRD 604", sheet 1. Utilizing the latest "state of the art" in micro-processor design and measuring technique, the benefits of the OMD-15 are:



OMD-15

- ◆ Easy to operate
- ◆ Improvement on Solids suppression
- ◆ Variable Parameters
- ◆ Compact Model
- ◆ 14 Segment LED's
- ◆ Reliable
- ◆ Light Weight (3,5 kgs)

SPECIFICATION OMD-15 SERIES

Range:	0 - 9,9 ppm
Accuracy:	Better than +/- 1 ppm insoluble Oil (with special calibration)
Degree of Protection:	IP 65
Size OMD-15:	175 x 190 x 220 mm (W x H x D)
Size OMD-15A:	210 x 330 x 220 mm (W x H x D)
Sample Temperature:	+1°C to +90°C
Alarm Contact Rating:	Potential-free 1 pole change-over contacts, 3 A / 24 V
Alarm Operating Points:	2 ppm (Factory Set) adjustable from 0,2 - 9,9 ppm
Alarm 1 & 2 Operating Delay:	2 - 20 sec. adjustable
Power supply:	24 Volt AC/DC, other voltages on request
Output Signal:	0 - 20 mA or 4 - 20 mA, reversible Ri < 500 Ω

(Change or amendment of specifications without notice.)

Additional Equipment like Sample Lift Pumps and special Coolers available on request.

Models: OMD-15 - without Autoclean-System
OMD-15A - with Autoclean-System

Contacts / Enquiries:

Agent:

DECKMA HAMBURG GmbH

Kieler Straße 316, 22525 Hamburg / Germany

Telephone: ++49 40 54 88 76 0
Telefax: ++49 40 54 88 76 10
e-Mail: post@deckma.com
Internet: www.deckma.com